

# Primary Wire

- > Single Conductor Copper Stranded
- > Polyvinyl Chloride Insulation
- > Flexible, Permanent Color & High Abrasion Resistance
- > Meets SAE Type GPT Specifications
- > Operating Temperatures of -20°F to 165°F



**"C" PACK**  
Bagged Coil Pack



**"PT" PACK**  
Clam Shell Coil Pack



**"J" SPOOL**  
Plastic "Junior" Spool



**"S" SPOOL**  
3" Plastic Spool

AWG	Part Number and Color Code										Add Suffix To Specify Packaging				
	Red	Yellow	Black	Green	Blue	Brown	White	Orange	Purple		"A" Reel	"S" Spool	"J" Spool	"C" Pack	"PT" Pack
8	81081	—	81083	—	—	—	—	—	—	—	250'	50'	5'	5'	5'
10	81101	81102	81103	81104	81105	81106	81107	—	—	—	500'	75'	10'	10'	10'
12	81121	81122	81123	81124	81125	81126	81127	—	—	—	500'	100'	15'	12'	12'
14	81141	81142	81143	81144	81145	81146	81147	81148	81149	—	1000'	100'	25'	20'	20'
16	81161	81162	81163	81164	81165	81166	81167	81168	81169	—	1000'	100'	35'	25'	25'
18	81181	81182	81183	81184	81185	81186	81187	—	—	—	1000'	100'	50'	35'	35'
20	81201	—	81203	—	—	—	—	—	—	—	1000'	100'	50'	50'	50'
22	81221	—	81223	—	—	—	—	—	—	—	1000'	100'	50'	40'	40'

## PRIMARY WIRE DISPLAY ASSORTMENTS

- > "C" Pack - #0006-L
- > "PT" Clam Shell - #0007-WPT
- > "S" Spooled Primary Wire - #0006-W

10 Through 18 Gauge - Assorted Colors  
Available For Immediate Shipment  
Consult Factory for Assortment Listings  
All Assortments Available Assembled on 2' x 2' Pegboard or Boxed Unassembled



**#0007-WPT**

## JUNIOR SPOOL ASSORTMENT

**#0006-J-10**

10 Junior Spools Per Assortment  
2 Spools Each 10 thru 18 Gauge  
Variety of Colors



## Starter Cable



Available In Black & Red

Rope Stranded Pure Copper Conductor  
Tough PVC Jacket  
Resists Acids, Oil & Abrasions  
Designed for Maximum Efficiency & Long Life

AWG	Color	Part #	Qty	Part #	Qty
00	Red	8090A	250'	8090S	50'
0	Red	8091A	250'	8091S	50'
1	Red	8092A	250'	8092S	50'
2	Red	8093A	250'	8093S	50'
4	Red	8094A	250'	8094S	50'
6	Red	8096A	250'	8096S	50'
000	Black	8098A	250'	8098S	50'
00	Black	8099A	250'	8099S	50'
0	Black	8100A	250'	8100S	50'
1	Black	8101A	250'	8101S	50'
2	Black	8102A	250'	8102S	50'
4	Black	8104A	250'	8104S	50'
6	Black	8106A	250'	8106S	50'

## Ignition Cable



### 7MM METALLIC CONDUCTOR IGNITION CABLE

Tinned Copper Wire Core  
High Dielectric Rubber Compound Insulation

AWG	Part #	Qty
7mm	8127S	100'



### 7MM DISTRIBUTOR RESISTANCE CORE IGNITION CABLE

Graphite Impregnated Glass Fiber Core  
High Dielectric Rubber Compound Insulation with Glass Fiber Braid  
Tough EPDM Rubber Outer Jacket

AWG	Part #	Qty
7mm	8128S	100'



### 8MM SILICONE SUPPRESSOR IGNITION CABLE

Fiberglass Stranded Core  
High Dielectric Rubber Compound Insulation with Fiberglass Fishnet  
500°F Gray Silicone Outer Jacket

AWG	Part #	Qty
8mm	8129S	100'

All Items with QT, KT or PT Suffix are Clam Shell Program Items.