

Booster Cables



#8172C 8 GA 12'
#8174C 6 GA 16'

Heavy Duty Bonded
Tangle Free
400 AMP Clamps
Extended Jaws For Side Mount



#8165G 4 GA 15'
#8165H 4 GA 30'

Heavy Duty 500 AMP Clamps
Bonded 4 AWG Cable
Flexible To -72°F
Replaceable Copper Jaws Available (#8169C)

Booster Clamps



Replacement Clamps & Jaws
For Cables 8165G & 8165H



Parrot Style with Jaws
500 AMP Clamps

Part #	Description	Qty
8167B	Black Clamp	1
8168R	Red Clamp	1
8169C	Jaw and Parts	1

Part #	Description	Qty
8170C	Red Clamp	1
8170PT	Red Clamp	1
8171C	Black Clamp	1
8171PT	Black Clamp	1


Battery Isolator Switch



#5575C (#5575PT)

Single Circuit Battery Master Switch
Provides Anti-Theft & Fire Protection
Isolates Battery Circuit
Detachable Key For Anti-Theft
Includes Weather Resistant Cap
Ideal for RV, Marine & Farm Equipment

Maximum Load (10 seconds):
12 volt 500 amp DC Momentary
Maximum Continuous Rating:
12 volt 350 amp DC Continual



Easy Installation

Electrical Tape



Tru-grip All Weather Black Vinyl Tape
Excellent Adhesive Qualities In All Types Of Weather
UL & CSA Approved
For Use At Not More Than 80°C (176°F)
Soft Polyvinyl 7 Mils Thick - 3/4" Wide - 60' Length
Rolls Individually Labeled & Wrapped

Packed 20 Rolls Per Display Box
200 Rolls (10 Boxes) Per Shipping Case

Part #	Qty
3460C	Box of 20 rolls
3460U	1-4 Cases
3460A	5+ Cases

Shrink Tubing



Measured By Inside Diameter Before Shrinking
Available in Kits -
#0003-ST, #0003-SR, #0003-SRB (Page 5)



#0630PT Mini Torch
#0640T Shrink Gun
(See Page 15)



WATERPROOF SHRINK TUBING

Rigid Polyolefin Dual Wall
Outer Wall Shrinks - Inner Wall Melts
Moisture Proof Upon Cooling
Shrink Ratio 3 to 1
Operating Temperature:
-67°F to 230°F (-55°C to 110°C)

BLACK RED

SINGLE WALL SHRINK TUBING
Flexible Polyolefin Single Wall Tubing
Shrink Ratio 2 to 1
Operating Temperature -67°F to 275°F (-55°C to 135°C)

BLACK

I.D.	Part #	Qty	Part #	Qty
1/8"	8219AA	100'	8219C	4-6"
1/8"	8219A	4'	8219PT	4-6"
3/16"	8220AA	100'	8220C	4-6"
3/16"	8220A	4'	8220PT	4-6"
1/4"	8221AA	100'	8221C	4-6"
1/4"	8221A	4'	8221PT	4-6"
3/8"	8222AA	100'	8222C	4-6"
3/8"	8222A	4'	8222PT	4-6"
1/2"	8223AA	100'	8223C	4-6"
1/2"	8223A	4'	8223PT	4-6"
3/4"	8224AA	100'	8224C	4-6"
3/4"	8224A	4'	8224PT	4-6"
1"	8225A	4'	—	—
1"	8225C	4-6"	8225PT	4-6"

RED

I.D.	Part #	Qty	Part #	Qty
1/8"	8250A	4'	8250C	4-6"
1/8"	—	—	8250PT	4-6"
3/16"	8251A	4'	8251C	4-6"
3/16"	—	—	8251PT	4-6"
1/4"	8252AA	100'	8252C	4-6"
1/4"	8252A	4'	8252PT	4-6"
3/8"	8253AA	100'	8253C	4-6"
3/8"	8253A	4'	8253PT	4-6"
1/2"	8254A	4'	8254C	4-6"
1/2"	—	—	8254PT	4-6"
3/4"	8255A	4'	8255C	4-6"
3/4"	—	—	8255PT	4-6"
1"	8256A	4'	8256C	4-6"
1"	—	—	8256PT	4-6"

I.D.	Part #	Qty	Part #	Qty
3/16"	8230A	4'	8260A	4'
3/16"	8230C	4-6"	8260C	4-6"
3/16"	8230PT	4-6"	8260PT	4-6"
1/4"	8231A	4'	8261A	4'
1/4"	8231C	4-6"	8261C	4-6"
1/4"	8231PT	4-6"	8261PT	4-6"
3/8"	8232A	4'	8262A	4'
3/8"	8232C	4-6"	8262C	4-6"
3/8"	8232PT	4-6"	8262PT	4-6"
1/2"	8233A	4'	8263A	4'
1/2"	8233C	4-6"	8263C	4-6"
1/2"	8233PT	4-6"	8263PT	4-6"
3/4"	8234A	4'	8264A	4'
3/4"	8234C	4-6"	8264C	4-6"
3/4"	8234PT	4-6"	8264PT	4-6"
1"	8235A	4'	8265A	4'
1"	8235C	4-6"	8265C	4-6"
1"	8235PT	4-6"	8265PT	4-6"

INSTALLATION:
Slide Tubing Over Wire
Crimp Terminal On Wire
Apply Heat 200°F to 300°F
Cool For Tough Insulation

PACKAGE OF ASSORTED SHRINK TUBING

Part #	Qty
8226C	4-6"
8226H	10-2"
8226PT	4-6"
8226KT	10-2"
8226QT	5-2"

All Items with QT, KT or PT Suffix are Clam Shell Program Items.