

Convolved Tubing & Accessories



Colored & Black Flexible Polyethylene Tubing
Tubing Split For Easy Wire Insertion
Operating Temperature -30°F to 200°F
See Page 24 & 25 for Accessories

I.D.	Color	Part #	Qty	Part #	Qty	Part #	Qty	Part #	Qty
1/4"	Black	5140AA	500'	5140A	50'	5140C	14'	5140PT	14'
1/4"	Yellow	—	—	5130A	50'	5130C	14'	5130PT	14'
1/4"	Blue	—	—	5135A	50'	5135C	14'	5135PT	14'
1/4"	Red	—	—	5150A	50'	5150C	14'	5150PT	14'
3/8"	Black	5141AA	500'	5141A	50'	5141C	10'	5141PT	10'
3/8"	Yellow	—	—	5131A	50'	5131C	10'	5131PT	10'
3/8"	Blue	—	—	5136A	50'	5136C	10'	5136PT	10'
3/8"	Red	—	—	5151A	50'	5151C	10'	5151PT	10'
1/2"	Black	5142AA	500'	5142A	50'	5142C	7'	5142PT	7'
1/2"	Yellow	—	—	5132A	50'	5132C	7'	5132PT	7'
1/2"	Blue	—	—	5137A	50'	5137C	7'	5137PT	7'
1/2"	Red	—	—	5152A	50'	5152C	7'	5152PT	7'
5/8"	Black	5144AA	250'	5144A	50'	5144C	6'	5144PT	6'
3/4"	Black	5143AA	250'	5143A	50'	5143C	5'	5143PT	5'
1"	Black	5145AA	100'	—	—	—	—	—	—
1 1/4"	Black	5146AA	100'	—	—	—	—	—	—
1 1/2"	Black	5147AA	50'	—	—	—	—	—	—
2"	Black	5148AA	50'	—	—	—	—	—	—
Assorted		0006-CV1		Package of 1/4", 3/8", 1/2", 5/8", 3/4"					

Black Polypropylene Connectors For Convolved Tubing
Accessories Measured By Tubing Diameter

END FITTING



Diameter	Part #	Qty
1/2"	5106A	25
1/2"	5106C	1
1/2"	5106PT	1

TEE FITTING



Left-Center-Right	Part #	Qty
3/8" - 3/8" - 3/8"	5110A	25
3/8" - 3/8" - 3/8"	5110C	1
3/8" - 3/8" - 3/8"	5110PT	1
1/2" - 1/2" - 1/2"	5111A	25
1/2" - 1/2" - 1/2"	5111C	1
1/2" - 1/2" - 1/2"	5111PT	1
3/4" - 3/8" - 3/4"	5112A	25
3/4" - 3/8" - 3/4"	5112C	1
3/4" - 3/8" - 3/4"	5112PT	1
3/4" - 1/2" - 3/4"	5113A	25
3/4" - 1/2" - 3/4"	5113C	1
3/4" - 1/2" - 3/4"	5113PT	1

OUTLET FITTING



Left - Right	Part #	Qty
1/2" - 1/2"	5107A	25
1/2" - 1/2"	5107C	1
1/2" - 1/2"	5107PT	1

Spi Wrap

Expandable Spiral Cut Polyethylene Wrap
Retains Strength Under Repeated Flexing
Operating Temperature -105°F to 215°F
Natural color

Measured By Outside Diameter
Of Unexpanded Wrap
(Wire Not Included)



PACKAGE OF ASSORTED SPI WRAP SIZES

Part #	Qty
5126C	15'
5126PT	15'

O.D.	Part #	Qty	Part #	Qty
1/8"	5118A	100'	—	—
3/16"	5119A	100'	—	—
1/4"	5120A	100'	—	—
1/4"	5120C	5'	5120PT	5'
3/8"	5121A	100'	—	—
3/8"	5121C	5'	5121PT	5'
1/2"	5122A	100'	—	—
1/2"	5122C	5'	5122PT	5'
3/4"	5123A	100'	—	—
1"	5124A	100'	—	—

Fabric Loom



Tough Flexible Loom
Easy Wire Insertion
Saturated With Asphalt Compound
For Moisture Proof
Non-Metallic Material Provides
Against Short Circuits
Maximum Temperature 350°F


I.D.	Part #	Qty	Part #	Qty
3/16"	8212A	250'	8212S	50'
1/4"	8213A	250'	8213S	50'
1/4"	8213C	10'	8213PT	10'
5/16"	8211A	250'	8211S	50'
3/8"	8214A	250'	8214S	50'
3/8"	8214C	7'	8214PT	7'
1/2"	8215A	250'	8215S	50'
1/2"	8215C	5'	8215PT	5'
5/8"	8216A	250'	8216S	50'
3/4"	8217A	250'	8217S	25'
1"	8218A	250'	8218S	25'

Grommets



Flexible Oil Resistant Vinyl Grommets
Insert Into Predrilled Holes
Guards Against Cut Or Frayed Wires
Operating Temperature -31°F to 160°F

Available In Kits
#0001-G, #0003-G & #0004-G (Page 2)



A - O.D. of Wire or Wires
B - Groove/Wall Thickness
C - I.D. of Pre-drilled Hole

PACKAGE OF ASSORTED GROMMET SIZES

Part #	Qty
6110C	15
6110PT	15
6126QT	6

A	B	C	Part #	Qty	Part #	Qty	Part #	Qty	Part #	Qty
1/8"	1/16"	1/4"	6115A	1000	6115D	20	6115PT	50	6115QT	7
1/8"	1/16"	1/4"	6115C	50	6115M	7	6115KT	20	—	—
3/16"	1/16"	5/16"	6116A	1000	6116D	18	6116PT	50	6116QT	6
3/16"	1/16"	5/16"	6116C	50	6116M	6	6116KT	18	—	—
1/4"	1/16"	3/8"	6117A	500	6117D	15	6117PT	50	6117QT	5
1/4"	1/16"	3/8"	6117C	50	6117M	5	6117KT	15	—	—
5/16"	1/16"	7/16"	6118A	500	6118D	10	6118PT	40	6118QT	5
5/16"	1/16"	7/16"	6118C	40	6118M	5	6118KT	10	—	—
3/8"	1/16"	1/2"	6119A	500	6119D	10	6119PT	40	6119QT	5
3/8"	1/16"	1/2"	6119C	40	6119M	5	6119KT	10	—	—
1/2"	1/16"	5/8"	6120A	250	6120D	8	6120PT	20	6120QT	3
1/2"	1/16"	5/8"	6120C	20	6120M	3	6120KT	8	—	—
25/64"	1/8"	21/32"	6121A	250	6121D	5	6121PT	15	6121QT	2
25/64"	1/8"	21/32"	6121C	15	6121M	2	6121KT	5	—	—
5/8"	1/16"	7/8"	6122A	100	6122D	4	6122PT	10	6122QT	2
5/8"	1/16"	7/8"	6122C	10	6122M	2	6122KT	4	—	—
11/16"	1/16"	1"	6123A	100	6123D	2	6123PT	5	6123QT	1
11/16"	1/16"	1"	6123C	5	6123M	1	6123KT	2	—	—
3/4"	1/8"	1-1/16"	6124A	100	6124D	2	6124PT	4	6124QT	1
3/4"	1/8"	1-1/16"	6124C	4	6124M	1	6124KT	2	—	—
1/2"	1/4"	13/16"	6125A	100	6125D	4	6125PT	6	6125QT	2
1/2"	1/4"	13/16"	6125C	6	6125M	2	6125KT	3	—	—
1"	1/8"	1-3/8"	6127A	25	6127C	3	6127PT	3	—	—

All Items with QT, KT or PT Suffix are Clam Shell Program Items.