


Closed End Connectors

Use When Wires From One General Direction Need To Be Joined & Terminated Together

Flared Nylon Cap
Electro-Tin Plated Copper Insert
Terminates Groups of 2-4 Wires
Insert Stripped Wires Into Connector Insert & Crimp On Insert
Max Operating Temp 221°F (105°C)



(Wire Not Included)

16-14 AWG		12-10 AWG		8 AWG	
Part #	Qty	Part #	Qty	Part #	Qty
1266A	1000	1366A	500	4066A	250
1266C	50	1366C	25	4066C	20
1266H	14	--	--	--	--
1266D	10	1366D	9	--	--
1266M	4	1366M	3	--	--
1266PT	50	1366PT	25	--	--
1266KT	10	1366KT	6	4066KT	1
1266QT	4	1366QT	3	--	--

Twist Connects

Metal Insert Grabs & Holds Wire Ends Tightly In Place
Easily Terminates Groups Of Multiple Wire Gauges
Screw Connectors Onto Ends of Stripped Wires
Includes Metal Insert Spring
Terminates Groups of Two to Four Wires
Max Operating Temp 221°F (105°C)



(Wire Not Included)

Color	Gauge	Part #	Qty	Part #	Qty	Part #	Qty
Assorted Sizes		1543C	25	--	--	1543PT	25
Gray	22-16 AWG	1545A	1000	1545H	20	1545PT	50
	Min 2 #22 Ga	1545C	50	1545D	15	1545KT	20
	Max 2 #16 Ga	--	--	1545M	6	1545QT	6
Blue	16-14 AWG	1544A	500	--	--	1544PT	25
	Min 2 #22 Ga	1544C	25	1544D	13	1544KT	14
	Max 3 #16 Ga	--	--	1544M	5	1544QT	5
Yellow	14-12 AWG	1546A	250	1546H	10	1546PT	15
	Min 3 #18 Ga	1546C	15	1546D	7	1546KT	6
	Max 2 #12 Ga	--	--	1546M	3	1546QT	3

Tap-In Connectors

No Wire Stripping Required On Tap-In Connectors

Insert Hot Line & Tap-In Wire
Compress Metal Clip With Pliers
Close Cover



Red
22-18 AWG

Part #	Qty
1558A	250
1558C	15
1558D	3
1558M	1
1558PT	15
1558KT	5
1558QT	1

Brown
18-14 AWG Tap-In
12-10 AWG Hot Line



Part #	Qty
1561A	100
1561C	5
1561D	2
1561PT	5
1561KT	2
1561QT	1

Yellow
12-10 AWG



Part #	Qty
1562A	100
1562C	5
1562D	3
1562PT	5
1562KT	2
1562QT	1



Blue 18-14 AWG

Part #	Qty	Part #	Qty
1560A	250	--	--
1560G	50	1560GT	50
1560C	15	1560PT	15
1560H	7	1560KT	5
1560D	5	--	--
1560M	2	1560QT	2

White
18-14 AWG Hot Line &
Tap-in Pass Through



Part #	Qty
1564A	250
1564C	15
1564D	4
1564PT	15
1564KT	2
1564QT	1



GEL-FILLED
Weatherproof
Blue

Part #	Qty
1565A	250
1565C	15
1565H	3
1565PT	15
1565KT	3

Snap T-Tap On Hot Wire
Closing Forms a Female Receptacle
Insert .250" Male Tab



Red 22-18 AWG		Blue 18-14 AWG		Yellow 12-10 AWG	
Part #	Qty	Part #	Qty	Part #	Qty
1567A	250	1568A	250	1569A	250
1567C	15	1568C	15	1569C	15
1567D	4	1568D	4	1569D	4
1567PT	15	1568PT	15	1569PT	15
1567KT	4	1568KT	4	1569KT	4
1567QT	2	1568QT	2	1569QT	2



Combo #1887

Insert Hot Line
Close Case
Tap-In With .157" Bullet



Combo #1880

Black 18-14 AWG	
Part #	Qty
1580A	200
1580C	10
1580D	3
1580PT	10
1580KT	2
1580QT	1

IDC Connector

INSULATION DISPLACEMENT CONNECTOR
Connects 2 or 3 Wire Ends
Self Stripping - Insert Wires & Compress Blue Top
Internal Grease Pocket Provides Moisture Resistant Seal



Blue
22-14 AWG

Part #	Qty
1556A	25
1556C	3
1556PT	3

Pin Connectors

Single Wire Disconnect For Use On Truck/Trailer Plugs
& European Style Terminal Blocks



Pins Measured By Diameter Of Tip

Red .08 Pin 22-16 AWG		Blue .08 Pin 16-14 AWG		Yellow .11 Pin 12-10 AWG	
Part #	Qty	Part #	Qty	Part #	Qty
1769A	1000	1869A	1000	1969A	500
1769C	50	1869C	50	1969C	50
1769D	12	1869D	12	1969D	8
1769M	5	1869M	5	1969M	4
1769PT	50	1869PT	50	1969PT	50
1769KT	12	1869KT	12	1969KT	10
1769QT	5	1869QT	5	1969QT	4

All Items with QT, KT, ET, GT or PT Suffix are Clam Shell Program Items.