

Starter Cable



Available In Black & Red

MADE IN USA



Solder Pellets Page 27

Rope Stranded Annealed Pure Copper Conductor
Tough Heat Resistant PVC Jacket
Ideal for Battery to Switch, Starter & Ground
For Use At 60 Volts or Less
Resists Acids, Oil, Abrasions & Handles Heavy Duty Demands
Designed for Maximum Efficiency & Long Life
Operating Temperature -58°F (-50°C) to 221°F (105°C)
Meets SAE J1127 & J378 Specifications

AWG	Color	Part #	Qty	Part #	Qty
00	Red	8090A	250'	8090S	50'
0	Red	8091A	250'	8091S	50'
1	Red	8092A	250'	8092S	50'
2	Red	8093A	250'	8093S	50'
4	Red	8094A	250'	8094S	50'
6	Red	8096A	250'	8096S	50'
0000	Black	8097A	100'	8097S	25'
000	Black	8098A	250'	8098S	50'
00	Black	8099A	250'	8099S	50'
0	Black	8100A	250'	8100S	50'
1	Black	8101A	250'	8101S	50'
2	Black	8102A	250'	8102S	50'
4	Black	8104A	250'	8104S	50'
6	Black	8106A	250'	8106S	50'

Welding Cable



Stays Flexible!

MADE IN USA

Fine Stranded Annealed Copper Core
EPR Jacket For Great Dielectric Strength,
Abrasion Resistance & Durability In Heavy Duty Use
Rated Up To 600 Volts
Excellent Flexibility In Hot & Cold Temps For Easy
Installation & Dependable Performance
Operating Temperature -58°F (-50°C) to 221°F (105°C)

AWG	Color	Part #	Qty	Part #	Qty
6	Black	8080AA	500'	8080A	100'
4	Black	8081AA	500'	8081A	100'
2	Black	8082AA	500'	8082A	100'
1	Black	8083AA	500'	8083A	100'
0	Black	8084AA	500'	8084A	100'
00	Black	8085AA	500'	8085A	100'
000	Black	8086AA	500'	8086A	100'
0000	Black	8087AA	500'	8087A	100'

Jacketed Multiple Conductor



#8130 - #8131 - #8132 - #8133 - #8134
Two Insulated Primary Wires
Black - White



#8135
Four Insulated Primary Wires
Red - Black - White - Green

Tough Gray Polyvinyl Outer Sheath
For Use At 60 Volts or Less
Can Withstand Extreme Abrasion & Adverse Weather Conditions
Operating Temperature -40°F (-40°C) to 221°F (105°C)
Inner Copper Core Wires Meet SAE J1128 & J378 Specifications

MADE IN USA

AWG	Cond	Part #	Qty	Part #	Qty
10	2	8130A	250'	8130C	10'
10	2	8130S	100'	8130PT	10'
12	2	8131A	250'	8131C	15'
12	2	8131S	100'	8131PT	15'
14	2	8132A	250'	8132C	25'
14	2	8132S	100'	8132PT	25'
16	2	8133A	250'	8133C	25'
16	2	8133S	100'	8133PT	25'
18	2	8134A	250'	8134C	25'
18	2	8134S	100'	8134PT	25'
16	4	8135A	250'	8135C	20'
16	4	8135S	100'	8135PT	20'

Speaker Wire



Two Clear Insulated Copper Wires
Bonded To Form Dual-Conductor Cord
Bare Copper Conductor & Tin Plated Conductor
Coded for Easy Identification
Easily Separated

MADE IN USA

AWG	Cond	Part #	Qty	Part #	Qty
22	2	8136A	250'	8136C	30'
22	2	8136S	100'	8136PT	30'
22	2	8136J	50'	—	—
18	2	8137A	250'	8137C	30'
18	2	8137S	100'	8137PT	30'
16	2	8138A	250'	8138C	25'
16	2	8138S	100'	8138PT	25'

Parallel Multi-Conductor



2 Conductor



3 Conductor



4 Conductor

"PVC" Insulated Primary Wires
Bonded To Form Parallel
Multi-Conductor Cables

Easily Separated
Uniquely Suited Where Multiple
Circuits Terminate In One Direction

For Use At 60 Volts or Less
Temp -40°F (-40°C) to 176°F (80°C)
Meets SAE J1128 & J378 Specifications

Use With Trailer Connectors
(Page 54)

MADE IN USA

AWG	Cond	Colors	Part #	Qty	Part #	Qty
14	2	Rd/Bk	8139A	250'	8139C	25'
14	2	Rd/Bk	8139S	100'	8139PT	25'
14	3	Gr/Yl/Br	8140A	250'	8140C	25'
14	3	Gr/Yl/Br	8140S	100'	8140PT	25'
14	4	Gr/Yl/Br/Wt	8141A	250'	8141C	25'
14	4	Gr/Yl/Br/Wt	8141S	100'	8141PT	25'
16	3	Gr/Yl/Br	8142A	250'	8142C	25'
16	3	Gr/Yl/Br	8142S	100'	8142PT	25'
16	4	Gr/Yl/Br/Wt	8143A	250'	8143C	25'
16	4	Gr/Yl/Br/Wt	8143S	100'	8143PT	25'
16	2	Yl/Br	8147A	250'	8147C	25'
16	2	Yl/Br	8147S	100'	8147PT	25'
18	2	Rd/Bk	8148A	250'	8148C	25'
18	2	Rd/Bk	8148S	100'	8148PT	25'

Trailer Cable



Flexible Copper Conductors - Color Coded PVC Insulation
Cabled With Stout Fillers & Bound With An Overwrap
Tough "Polar Flex" Outer Jacket - For Use At 60 Volts or Less
Operating Temp -85°F (-65°C) to 176°F (80°C) (#8158 -58°F (-50°C))
Inner Wires Meet SAE J1128 & J378 Specs (#8158 also Meets SAE J2394)

All Weather Heavy Duty Cable

MADE IN USA



AWG	Cond	Colors	Part #	Qty	Part #	Qty	Part #	Qty
12	6	Rd/Bk/Br/Gr/Yl/Bl	8150A	250'	8150S	100'	—	—
10	1	Wh	—	—	—	—	—	—
14	6	Rd/Bk/Br/Gr/Yl/Wh	8151A	250'	8151S	100'	8151C	25'
14	4	Rd/Bk/Br/Wh	8152A	250'	8152S	100'	—	—
14	3	Bk/Gr/Wh	8153A	250'	8153S	100'	—	—
16	4	Rd/Bk/Br/Wh	8154A	250'	8154S	100'	8154C	25'
16	6	Rd/Wh/Bk/Br/Gr/Yl	8155A	250'	8155S	100'	—	—
14	7	Rd/Bk/Br/Gr/Yl/Bl/Wh	8157A	250'	8157S	100'	—	—
12	4	Bk/Br/Gr/Yl	—	—	—	—	—	—
10	2	Rd/Bl	8158A	250'	8158S	100'	—	—
8	1	Wh	—	—	—	—	—	—
10	2	Bk/Wh	—	—	—	—	—	—
12	1	Bl	—	—	—	—	—	—
14	4	Rd/Br/Gr/Yl	—	—	—	—	—	—

7-Way ABS Truck Cable (Green Jacket)

7-Way RV Cable (Black Jacket)