


Solder & Heat Shrink Butt Connector



Intermingle & Overlap Stripped Wires In Center of Solder Ring
Slowly Apply Heat Until Solder Ring Melts
Continue Heating Tubing Until Adhesive Flows & Tubing Shrinks

Pre-Fluxed Solder Ring
Translucent & Adhesive Lined Polyolefin Shrink Sleeve
Maximum Electrical Rating 600 volts - Tensile Strength 2200 psi
Solder Melt Point 300°F (149°C) - Insulation Shrink Temp 275°F (135°C)
Operating Temperature -67°F to 230°F (-55°C to 110°C)

NEW



Soldering Gives Strong Vibration Resistant Life To Each Connection

Clear		Red		Blue		Yellow	
26-22 AWG	Part # Qty	22-16 AWG	Part # Qty	16-14 AWG	Part # Qty	12-10 AWG	Part # Qty
2247A	100	2252A	100	2262A	100	2272A	100
2247G	25	2252G	25	2262G	25	2272G	25
2247GT	25	2252GT	25	2262GT	25	2272GT	25
2247C	5	2252C	5	2262C	5	2272C	5
2247PT	5	2252PT	5	2262PT	5	2272PT	5

Crimp-Solder-Heat Shrink Butt Connector



Pre-Fluxed Solder Ring



*NEW #0385T Tool
Crimps Heat Shrink Terminals
22-8 Ga (Page 20)*

Insert & Intermingle Stripped Wires In Connector & Crimp
Apply Heat Until Pre-Fluxed Solder Ring Melts
Continue Heating Tubing Until Adhesive Flows & Tubing Shrinks
Cool For a Perfect Watertight Connection

Seamless Copper Butt Connectors - Wire Stop Prevents Over-Insertion
Translucent & Adhesive Lined Polyolefin Shrink Sleeve
Window in Connector Allows Visual Inspection of Solder Flow
Maximum Electrical Rating 900 volts - Tensile Strength 2200 psi
Solder Melt Point 300°F (149°C) - Insulation Shrink Temp 275°F (135°C)
Operating Temperature -67°F to 230°F (-55°C to 110°C)



*Using a Crimpable Connector
Will Hold Wire in Place
While Solder is Melting*

Clear		Red		Blue		Yellow	
24-22 AWG	Part # Qty	22-16 AWG	Part # Qty	16-14 AWG	Part # Qty	12-10 AWG	Part # Qty
2248A	100	2254A	100	2264A	100	2274A	100
2248G	25	2254G	25	2264G	25	2274G	25
2248GT	25	2254GT	25	2264GT	25	2274GT	25
2248C	5	2254C	5	2264C	5	2274C	5
2248PT	5	2254PT	5	2264PT	5	2274PT	5

Solder & Heat Shrink Kits

Soldering Gives Strong Vibration Resistant Life To Each Connection



#0002-SS



#0003-SS



#0004-SS

#0002-SS CRIMP-SOLDER-HEAT SHRINK BUTT CONNECTORS

22-24, 22-16, 16-14 & 12-10 AWG Crimp & Heat Shrink Butt Connectors
70 pieces 6-1/2" x 3-1/2" Plastic Kit Refill Packs Page 9
Includes: 2248 2254 2264 2274

#0003-SS SOLDER & HEAT SHRINK TERMINAL KIT

Solder Shrink Terminals and Crimp & Solder Shrink Butt Connectors
54 pieces 10-3/4" x 7" Plastic Kit Refill Packs Page 9 & 10
Includes: 2254 2264 2274 2812 2818 2819 2821 2822 2823
2825 2828 2829 2831 2832 2834 2835 2838 2839

#0004-SS SOLDER & HEAT SHRINK TERMINAL KIT

120 Solder Shrink Terminals -15 Crimp & Solder Shrink Butt Connectors
13-1/2" x 9-1/2" Metal Kit Refill Packs Page 9 & 10
Includes: 2254 2264 2274 2810 2811 2812 2813 2816
2818 2819 2821 2822 2823 2825 2826 2828
2829 2831 2832 2834 2835 2836 2838 2839

All Items with QT, KT, ET, GT or PT Suffix are Clam Shell Program Items.